



**AT1300B AT1300BL**

# **1" Drive Impact Wrench (Blue-Point®)**

## **Features and Benefits**

- Durable and powerful pin-less clutch mechanism
- Ergonomic housing design with steel protector ring
- High performance motor maximizes output torque
- Side mounted handle for better operator control
- Optional internal/external trigger set
- (3) forward and (3) reverse speeds
- One year warranty



**AT1300B**



**AT1300BL**

**CE** CE - DE, ES, FR, IT, GB, NL

Country of Origin: TAIWAN

Snap-on and Blue-Point are trademarks, registered in the United States and other countries, of Snap-on Incorporated. All other trademarks are marks of their respective holders. ©Snap-on Incorporated 2018. All rights reserved.  
Snap-on, 2801 80th Street, Kenosha, WI 53143 www.snapon.com

**September 2018**  
**Page 1 of 2**





# AT1300B AT1300BL

## ⚠ WARNING



• Power tools can cause flying particles  
Wear safety goggles (Users and bystanders).  
*Flying particles can cause injury.*



• Power tools generate noise  
Wear hearing protection (Users and bystanders).



*Prolonged exposure to noise can cause hearing loss.*

• Power tools vibrate  
Avoid prolonged exposure to vibration.  
*Prolonged exposure to vibration can cause injury.*

• Improper use of power tools and accessories can cause broken tools

Do not use without all guards in place.  
Use accessories rated at tool RPM.  
Read and follow instructions before using power tools.

*Broken tools can cause injury*  
Read additional safety warnings on pages W1 to W4 in Catalog 1400

## Specifications

Drive Size, inches (mm)	1 (25)
Recommended Hose Size, inches (mm)	1/2 (13)
Air Inlet Thread Size	1/2" - 14 NPT
Sound Level dB(A) Pressure	108.9
Length, inches (mm)	13.59 (345)
Maximum Torque, ft-lb (N•m)	2000 (2712)
Weight, lb (kg)	23.18 (10.50)
Free Speed, RPM	5000
Vibration Level, m/s <sup>2</sup>	12.01
Air Consumption, Free Speed, CFM (SCFM) [l/min]	10.8 (-) [305.82]
Extended Anvil Length, inches (mm)	6 (152)
Anvil Type	Friction Ring w/Thru Hole