



CT761AQC

14.4 V 1/4" Drive MicroLithium Quick Change Cordless Impact Wrench Kit

Features and Benefits

- 60 ft-lb torque output
- 2,500 RPM free speed
- 55-minute charge time
- Digital variable-speed toggle style trigger for precise control
- Tri-beam headlights illuminate work area
- Built-in brake stops the tool from throwing sockets and fasteners
- Over current and thermal protection for the motor
- Under voltage protection will not overdraw the battery
- Built-in gauge lets you know the state of the battery charge
- Screened motor keeps debris from entering critical components
- Cushion grip handle provides positive tool control with less fatigue
- Over and under temperature protection keeps tool operating at peak efficiency



CE - DE, ES, FR, IT, GB, NL & JP

Country of Origin: CHINA



Snap-on is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All other trademarks are marks of their respective holders.
©Snap-on Incorporated 2017. All rights reserved.
Snap-on, 2801 80th Street, Kenosha, WI 53143 www.snapon.com

May 2018
Page 1 of 4
Revised 7/25/2018



Applications

Fender bolts
Valve cover bolts
Splash shield removal & installation
12mm Oil & transmission pan bolts
Water pump pulley bolts
Under dash fasteners
Fan shroud bolts
Installing door lock assemblies
Interior seat removal & installation
Small engine repair

ATV wheel lug nuts

-Polaris®/Rhino® (30-40 ft-lb)

Motorcycle Applications

Harley® Engine covers (14-21ft-lb)
-Inner rocker cover (135-155 in-lb)
-Brake caliper bolts (17-21 ft-lb)
-Axle nuts (60 ft-lb)
-Exhaust pipes to heads (15 ft-lb)

Briggs & Stratton® Engine Applications

-Head (up to 35 ft-lb)
-Connecting rod (100-175 in-lb)

Tecumseh® Engine Applications

-Flywheel nut (35 ft-lb)
-Cylinder head (200-240 in-lb)
-Connecting rod (105-210 in-lb)

Ford® 4.6 liter V8 Engine Applications

-Valve cover (71-106 in-lb)
-Intake manifold (71-89 in-lb)
-Oil pan (15-22 ft-lb)
-Water pump pulley (15-22 ft-lb)
-Water pump to block (15-22 ft-lb)
-Fuel injector rail (71-89 in-lb)
-Throttle Body (71-106 in-lb)
-Ignition coil brackets (15-22 ft-lb)
-Engine front cover (15-22 ft-lb)
-Crank shaft side bolts (14-17 ft-lb)
-Serpentine belt pulley (15-22 ft-lb)



CT761AQC

Included Components

- CT761AQCDB Impact Wrench
- CTC772A Charger
- CTB8172BK 14.4 V Battery(2)
- CTUTOTEABK Tote Bag



SDMEXT27K



CTL761



CT761DB

Optional Accessories

- SDMEXT27K - Adaptor Bit Set
- SDML19KT - Long Power Bit Set
- YA52PBSQC - Power Bit Set

Related Items

- CT761ADB 3/8" Impact
- CTR761C 3/8" Ratchet
- CTS761ADB 1/4" Screwdriver
- CTPP761ADB Polish/Prep Tool
- CTRS761ADB Saw
- CDR761BDB Drill
- CTL761 Flashlight
- CTLUH761 Underhood Light



CTR761BDB



YA52PBSQC





Specifications

CT761AQC

Anvil Type	1/4" Hex Quick Change
Battery (Quantity)	CTB8172BK (2)
Battery Type	MicroLithium 2.0 Ah
Battery Voltage	14.4
Blows Per Minute, BPM	3,000
Charge Time (minutes)	55
Charger	CTC772A
Free Speed, RPM	2,500
Height, inches (mm)	7.8 (198)
Length, inches (mm)	6.3 (160)
Hex Drive, inches	1/4" Hex Quick Change
Tool Only	CT761AQCDB
Torque Output, ft-lb (N•m)	60 (81)
Tote Bag	CTUTOTEABK
Warranty (Battery), years	1
Warranty (Tool and Charger), years	1
Weight w/Battery, lb (kg)	2.5 (1.1)
Width, inches (mm)	1.9 (48)

WARNING



- Power tools can cause flying particles
Wear safety goggles (Users and bystanders).
Flying particles can cause injury.



- Power tools generate noise
Wear hearing protection (Users and bystanders).



- Prolonged exposure to noise can cause hearing loss.

- Power tools vibrate
Avoid prolonged exposure to vibration.
Prolonged exposure to vibration can cause injury.

- Improper use of power tools and accessories can cause broken tools

Do not use without all guards in place.
Use accessories rated at tool RPM.
Read and follow instructions before using power tools.

Broken tools can cause injury
Read additional safety warnings on pages W1 to W4 in Catalog 1300

