



S6189 Dzus® Fastener Information

	A	B	L	
	Diameter	Length 1	Length 2	
S6189				
AJ3-25	0.1875	0.08	0.25	oval head
AJ4-25	0.25	0.10	0.25	oval head
AJ3-40	0.1875	0.20	0.40	oval head
AJ4-50	0.25	0.25	0.50	oval head
FJ3-30	0.1875	0.15	0.30	flush head
FJ4-35	0.25	0.18	0.35	flush head
FJ4-50	0.25	0.25	0.50	flush head
FJ3-40	0.1875	0.02	0.40	flush head
S6180				
AJ5-70	0.3125	0.40	0.70	oval head
AJ7-40	0.4375	0.19	0.40	oval head
AJ6-35	0.375	0.15	0.35	oval head
AJ6-70	0.375	0.35	0.70	oval head
AJ7-70	0.4375	0.35	0.70	oval head
AJ5-30	0.3125	0.13	0.30	oval head
FJ5-60	0.3125	0.30	0.60	flush head
FJ6-70	0.375	0.35	0.70	flush head
FJ7-50	0.4375	0.25	0.50	flush head
FJ7-70	0.4375	0.35	0.70	flush head
FJ5-40	0.3125	0.23	0.40	flush head
FJ6-50	0.375	0.25	0.50	flush head

Do not use slotted screwdrivers on Dzus® style fasteners as it may cause damage to the fastener.