



Snap-on[®] Reversible Wire Twister

WTG8
WTG10

One-Handed Operation for Improved Productivity

Features and Benefits

- Simple operation with a one-handed locking function
- Spring loaded handles automatically open when lock is released
- Jaw tips designed for precision work and hard to reach areas
- Reversible trigger makes it easy to switch between right and left applications with one hand
- Designed to hold clipped wire, reducing the likelihood of F.O.D. (foreign object damage)
- Ergonomic handle reduces user fatigue



CE – Not Required

Country of origin: France



WTG8
WTG10

Specifications

Stock No.	Description	Length
WTG8	8" Reversible Wire Twister L/R with F.O.D. Wire: Ø 0,4 mm to Ø 0,8 mm - .015" to .031"	8" – 203 mm
WTG10	10" Reversible Wire Twister L/R with F.O.D. Wire: Ø 0,6 mm to Ø 1,2 mm - .024" to .047"	10" – 254 mm

WARNING



- Broken tips or cut material can fly

Wear safety goggles (User and Bystander)



Flying material can cause injury
Read additional safety warnings on pages W1 to W4 in Catalog 1300



WT105-2004



WT105-2516

Related Items

Safety Wire

Stock No.	Wire Size, inches	Approximate Wire Length, ft	Container
WT105-2004	0.020	230	1/4 lb Spool
WT105-3204	0.032	90	1/4 lb Spool
WT105-4204	0.041	55	1/4 lb Spool
WT105-2016	0.020	937	1 lb Canister
WT105-2516	0.025	599	1 lb Canister
WT105-3216	0.032	366	1 lb Canister
WT105-4116	0.041	223	1 lb Canister
WT105-5116	0.051	—	1 lb Canister

Meets NASM20995 and MS20995C specifications plus conforms to ASTM580 Materials S30400